

# Configuración de data-sources

## 1. Desarrollo

```
<data-source
class="oracle.jdbc.pool.OracleDataSource"
name="CodappDS"
location="jdbc/CodappDS"
connection-driver="oracle.jdbc.driver.OracleDriver"
username="scott"
password="tiger"
url="jdbc:oracle:thin:@(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=backdes1.dga.es)(
PORT=1522))(CONNECT_DATA=(SERVICE_NAME=desapp0.dga.es)))">
</data-source>

<data-source
class="oracle.jdbc.pool.OracleDataSource"
name="CodappDS"
location="jdbc/CodappDS"
connection-driver="oracle.jdbc.driver.OracleDriver"
username="scott"
password="tiger"
url="jdbc:oracle:thin:@(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=backdes1.dga.es)(
PORT=1523))(CONNECT_DATA=(SERVICE_NAME=desapp1.dga.es)))">
</data-source>
```

## 2. Preproducción

```
<data-source
class="oracle.jdbc.pool.OracleDataSource"
name="CodappDS"
location="jdbc/CodappDS"
connection-driver="oracle.jdbc.driver.OracleDriver"
username="scott"
password="tiger"
url="jdbc:oracle:thin:@(DESCRIPTION=(LOAD_BALANCE=on)
(ADDRESS=(PROTOCOL=TCP)(HOST=vir_backpre1.dga.es)(PORT=1522))
(ADDRESS=(PROTOCOL=TCP)(HOST=vir_backpre2.dga.es)(PORT=1522))
(CONNECT_DATA=(SERVICE_NAME=preapp0.dga.es)))">
<property name="connectionCacheName" value="ICC"/>
<property name="connectionCachingEnabled" value="true"/>
<property name="fastConnectionFailoverEnabled" value="true"/>
</data-source>

<data-source
class="oracle.jdbc.pool.OracleDataSource"
name="CodappDS"
location="jdbc/CodappDS"
connection-driver="oracle.jdbc.driver.OracleDriver"
username="scott"
password="tiger"
url="jdbc:oracle:thin:@(DESCRIPTION=(LOAD_BALANCE=on)
(ADDRESS=(PROTOCOL=TCP)(HOST=vir_backpre1.dga.es)(PORT=1523))
(ADDRESS=(PROTOCOL=TCP)(HOST=vir_backpre2.dga.es)(PORT=1523))
(CONNECT_DATA=(SERVICE_NAME=preapp1.dga.es)))">
<property name="connectionCacheName" value="ICC"/>
<property name="connectionCachingEnabled" value="true"/>
<property name="fastConnectionFailoverEnabled" value="true"/>
</data-source>
```

### 3. Producción

```
<data-source
class="oracle.jdbc.pool.OracleDataSource"
name="CodappDS"
location="jdbc/CodappDS"
connection-driver="oracle.jdbc.driver.OracleDriver"
username="scott"
password="tiger"
url="jdbc:oracle:thin:@(DESCRIPTION=(LOAD_BALANCE=on)
(AADDRESS=(PROTOCOL=TCP)(HOST=vir_backpro1.dga.es)(PORT=1522))
(AADDRESS=(PROTOCOL=TCP)(HOST=vir_backpro2.dga.es)(PORT=1522))
(CONNECT_DATA=(SERVICE_NAME=proapp0.dga.es)))">
<property name="connectionCacheName" value="ICC"/>
<property name="connectionCachingEnabled" value="true"/>
<property name="fastConnectionFailoverEnabled" value="true"/>
</data-source>

<data-source
class="oracle.jdbc.pool.OracleDataSource"
name="CodappDS"
location="jdbc/CodappDS"
connection-driver="oracle.jdbc.driver.OracleDriver"
username="scott"
password="tiger"
url="jdbc:oracle:thin:@(DESCRIPTION=(LOAD_BALANCE=on)
(AADDRESS=(PROTOCOL=TCP)(HOST=vir_backpro1.dga.es)(PORT=1523))
(AADDRESS=(PROTOCOL=TCP)(HOST=vir_backpro2.dga.es)(PORT=1523))
(CONNECT_DATA=(SERVICE_NAME=proappl.dga.es)))">
<property name="connectionCacheName" value="ICC"/>
<property name="connectionCachingEnabled" value="true"/>
<property name="fastConnectionFailoverEnabled" value="true"/>
</data-source>
```